



INTEGRATED SYSTEM



TID-101

The TID-101 is a versatile public address pre-amplifier unit. The Signal Manager comes with a built-in 12 zone line selector and is scalable with external TSS-112 Line Selectors for a maximum of 60 zones. It is designed to be used with external power amplifiers making it a highly scalable suitable for any medium - to - large scale projects. It can be supplemented by a host of TPTG products.

FEATURES

- 12 zones speaker line selector (can be extended to 60 zones with TSS 122).
- BGM broadcast with 4 paging priority levels (Remote Mic, LINE1, Fire Alarm, Firemen's Mode, Handheld Mic.)
- Supports up to 8 TID-06 remote microphone.
- Built-in ascending & descending chimes for remote microphone paging.
- Interface with TID-102 for 12 zones (N-1, N, N+1) remote zone trigger (can be extended to 60 zones with TSS 122).
- Built-in siren tone.
- Attenuator override trigger output.

Technical Specification

TID-101	
Output Zones	12 Zone
Frequency Responses	20 Hz - 20 kHz
Input Sensitivity	Remote Mic 0 dB Balanced Line 1 0 dB Balanced AUX 1 - 3 RCA Connector, -20 dB Stereo
REC OUT	0 dB Balanced
Protection Circuit	Over current & short circuit protection with resettable fuse
Power Requirement	24 Vdc, 0.5 A
Dimensions (W x H x D)	430 x 87 x 200 mm
Material & Finish	Mild Steel Casing, Textured Black
Weight	5.0 kg