



INTEGRATED SYSTEM



The Integrated System Manager Series was developed with a clear objective, a Public Address System that was reliable and easy to use. A single box solution suitable for virtually any small-to-medium scale Public Address system application. The Integrated System Manager Series consist of the Master Unit with a built in power amplifier making it an extremely easy to deploy standalone PA System.

FEATURES

- Built in 600W power amplifier with 12 Zones speaker line outputs (Can be extended to 24 zones with TID-206E).
- Internal amplifier monitoring and standby amplifier changeover and Internal amplifier overload protection.
- BGM broadcast with 4 paging priority levels (Remote Mic, LINE 1, Fire Alarm, Firemen's Mode and Handheld Mic).
- Supports up to 8 TID-06 remote microphone. Built-in ascending and descending chimes for remote microphone paging.

- Interface with TID-102 for 12 Zones (N+1, N, N-1) remote zone trigger (Can be extended to 24 Zones with TID 206E).
- Built in siren tone.
- Attenuator override trigger output.
- Internal fan.

Technical Specification

TID-206	
Rated Power Output	600 W at 100 V line
Output Zones	12 Zone
Frequency Responses	20 Hz - 20 kHz
Input Sensitivity	Remote Mic 0 dB Balanced Line 1 0 dB Balanced AUX 1 - 3 RCA Connector, -20 dB Stereo
REC OUT	0 dB Balanced
Amplifier Changover	Built-in
Protection Circuit	Over current & short circuit protection with resettable fuse
Power Requirement	220 ~ 250 Vac, 50/60 Hz or 24 Vdc, 25 A
Dimensions (W x H x D)	430 x 132 x 500 mm
Material & Finish	Mild Steel Casing, Textured Black
Weight	26 kg