

## TNAC-04 4-CHANNEL NETWORK AMPLIFIER CHANGEOVER PANEL



NETWORK SYSTEM



TNAC-04

The TNAC-04 4-Channel Network Amplifier Changeover Panel unit provides monitoring and surveillance of power amplifiers within a project via the LAN. The unit is capable of monitoring up to 4 units of power amplifiers for faults. Upon fault detection the unit will automatically changeover the faulty amplifier to a standby amplifier and at the same time report the fault to the TNSM-01 Network System Manager or Network Paging Microphone.

### FEATURES

- Monitors up to 4 units of amplifier.
- Handles up to 1200W per-monitoring channel.
- Automatic switchover to a standby amplifier upon detection of a fault.
- Feedback of amplifier status via TCP/IP LAN.

# TNAC-04 4-CHANNEL NETWORK AMPLIFIER CHANGEOVER PANEL

## Technical Specification

	TNAC-04
Network Interface	10/100 Mbps Ethernet TCP/IP
No. of channels per unit	4 Channels Duty, 1 Standby
Max. power handling per channel	1200W
Indicators	Power, 5 Bi-Colour indicators for 4 Duty and 1 Standby amplifier status
Power Requirements	24Vdc (Regulated), 0.2A
Dimensions (W x H x D)	483 x 44 x 150 mm