

TNPP-10 NETWORK PAGING MICROPHONE



NETWORK SYSTEM



The TNPP-10 is a state of the art touchscreen based network paging console unit. It allows the user to operate the unit as well as select the zones via a user friendly GUI. From the GUI the operator will be able to make zone selection individually or in pre-defined groups based on the client's requirement. Being a network enabled console, the unit can be connected or relocated anywhere within the project without hassle - simply by connecting to the LAN's data point. Future upgrade to the unit will also allow the unit to communicate and TNPP-10 makes announcements via WIFI connection.

FEATURES

- Touchsreen based paging console.
- User friendly GUI.
- Select zones individually or in pre-programmed groups.
- System status and monitoring via the GUI.
- Hassle free LAN connection, easily relocated just connect it into the LAN datapoint.



TNPP-10 NETWORK PAGING MICROPHONE

NETWORK SYSTEM

Technical Specification

	TNPP-10
Network Interface	RJ45 10/100 Mbps Ethernet TCP/IP WIFI Connectivity
Touchscreen Dimension	9.7 inch
Microphone	Non-removable condenser gooseneck microphone with windshield
Power Requirements	5Vdc (Regulated)
Dimensions (W x H x D)	298 x 154 x 130 mm
Weight	1.6 kg